C14 to C19 Power Cord

Overview

Wave2Wave.io can offer optional lengths and various colors power cords. The W2W Power Cord is an ideal solution for connecting any server or networking device. IEC 60320 C14 to IEC 60320 C19 power cord is designed for connecting network switch, UPS, PDU.



IEC 60320 C14 IEC 60320 C19

Features & Benefits

- IEC 60320 C14 to IEC 60320 C19 power cord commonly used for network switch, UPS, PDU.
- Fully molded ergonomic design with 100% hipot testing on all cords.
- Carries UL certifications as well as RoHS and REACH compliance.

Applications

- Connect network switch, UPS, PDU.
- Extend an existing power connection.

Performance Specifications

Connecter 1	IEC 60320 C14	
Connecter 2	IEC 60320 C19	
Cable gauge	18AWG	14AWG
Cable outside diameter	Φ7.8±0.2mm	Φ9.3±0.2mm
Cable jacket	SJT	
Jacket material	PVC	
Max amperage and voltage	10A-250V	15A-250V

Product Selection

Part Number: 79C14C19-AB-CDEF

A (Cable jacket)	B (Cable gauge)	CD	EF (Cable length) (FT/Meter)
J(SJT)	4(14AWG)	BK(Black)	6(6 FT)
	8(18AWG)	RD(Red)	8(8 FT)
			10(10 FT)
			1.5M(1.5 Meter)

Standards Compliance

- IEC 60320.
- RoHS