CABLING123®
A WAVE2WAVE COMPANY

Power Cord

Overview

The Cabling123® can offer optional lengths and various colors power cords. Power Cord is an ideal solution for connecting any server or networking device. IEC 60320 C15 to NBR 14136 power cord is designed for connecting network switch, UPS, PDU.



Features & Benefits

- IEC 60320 C15 to NBR 14136 power cord commonly used for network switch, UPS, PDU.
- Fully molded ergonomic design with 100% hipot testing on all cords.
- Meet to RoHS and REACH compliance.

Applications

- Connect network switch, UPS, PDU.
- Extend an existing power connection.

Specification

Connecter 1	IEC 60320 C15	
Connecter 2	NBR 14136	
Cable gauge	18AWG	14AWG
Cable outside diameter	Φ7.8±0.2mm	Φ9.3±0.2mm
Cable jacket	H05VV-F	
Jacket material	PVC	
Max amperage and voltage	10A-250V	15A-250V

Standards Compliance

- IEC 60320.
- RoHS.

RoHS

Product Selection

Part Number: 79C15NBR-AB-CDEF

A	B	CD	EF
Cable jacket	Cable guage		Cable length(FT/Meter)
J(SJT)	4(14AWG)	BK(Black)	6(6 FT)
H(H05VV-F)	8(18AWG)	RD(Red)	8(8 FT)
			10(10 FT)
			1.5M(1.5 Meter)